



Robin Engine EY20D



Rubber Hose



Vibrator Needles
Models TCV 32, TCV 38, TCV 45, TCV 60

Models Concrete Vibrator with Poker

(High frequency electric vibrator also available upon request.)

Features

- Heavy duty, fixed frame concrete vibrator with high frequency induction hardened cap and body for high performance.
- High tension spring provides better vibration and longer machine life.
- Four vibrator needles available ranging from 32 mm to 60 mm with a choice of 6 or 10 m rubber hose.
- Comes with either Dynapac housing and coupling or pin-type coupling.
- Petrol or diesel engine, models are efficient, powerful, and extremely durable.

Specifications

Needle Technical Data

	TCV 32	TCV 38	TCV 45	TCV 60
Vibrator Head Diameter	32 x 480 mm	38 x 500 mm	45 x 505 mm	60 x 505 mm
Flexible Shaft Diameter	10 mm	10 mm	612 mm	12 mm
Rubber Hose Diameter	28 mm	28 mm	32 mm	32 mm
Amplitude	1.2 mm	1.6 mm	2.0 mm	2.4 mm
Vibration Per Minute (VPM)	9,000 - 12,500	9,000 - 12,500	9,000 - 12,500	9,000 - 12,500
Shaft Set Weight	17 Kg	17.5 Kg	18 Kg	23.5 Kg

September 07

Maxiito is the trading name of El Mechana Technical Equipment LLC for construction equipment

El Mechana Technical Equipment LLC
PO Box 181216
Dubai, United Arab Emirates

For a job well done, we are the one

Tel: +971 4 338 5141
Fax: +971 4 338 5142
Email: maxiito@maxiito.com

www.maxiito.com